

Agitating Ultrasonic Cleaning Systems

AgiSonic

Standard Features:

- 92, 123, 202 gallon capacities with platform load up to 5001bs.
- All Stainless Steel construction
- Single frequency @ 40 kHz
- High performance ultrasonics, universal "U1B" transducers
- Filtration, Surface Sparger, and Oil Skimmer
- User-friendly digitally controlled interface for heat, ultrasonics, and timer
- Liquid Level Protection for heater, pump, and ultrasonics
- Parts Basket
- Standard in 208V, 3 Phase

Optional Features:

- 25 kHz
- Rinse Tank
- Add'l Parts Basket
- Load/Unload Table
- Roller on Basket Platform
- Roller Conveyor Between Tanks
- Spray Wand
- 240V, 480V or 575V Power Supply



RANSOHOFF



**BLACKSTONE-NEY
ULTRASONICS**



CTG ASIA

Technical Specifications

AgiSonic 3000

AgiSonic 4000

AgiSonic 5000

Gallon Capacity	92	123	202
Maximum Parts Load	125 lbs.	125lbs.	500lbs.
Ultrasonics (40kHz)	3,000 W	4,000W	5,000W
Heat	6,000 W	9,000W	12,000W
Power Requirement	208V, 3Ø, 60Hz	208V, 3Ø, 60Hz	208V, 3Ø, 60Hz
Amperage	30 FLA	45 FLA	50 FLA
Total Liquid Depth	24"	24"	25"
Working Agitation Depth	17"	17"	18"
Agitation Stroke	2" - 6"	2" - 6"	2" - 6"
Shop Air Required	80 psi	80 psi	80 psi
Working Tank (LR x FB)	31" x 22"	35" x 27"	44" x 36"
Overall Unit (LR x FB x H)	38" x 51" x 68"	42" x 56" x 68"	56" x 78" x 79"
Basket (LR x FB)	26" x 18" x 8"	30" x 23" x 8"	40" x 30" x 8"

powered by



generators.



RANSOHOFF



**BLACKSTONE-NEY
ULTRASONICS**



CTG ASIA