

# Aqueous Rotating Table Cabinet Washer

## WashMaster™ Series



### WashMaster Model CW-35

- 35" table diameter and 19" work height-provides sufficient room to accommodate large loads
- Unique "Kwik Kleen" dual spray pump feature-speeds cleaning and ensures maximum up-time
- Stainless steel construction - provides a lifetime of reliable performance
- Heavy-duty rotating work table with positive gear motor drive - up to 440 lb. load capacity



### WashMaster Model CW-23

- 23" table diameter and 13" work height-to accommodate smaller part configuration
- Stainless steel construction - provides a lifetime of reliable performance
- Heavy-duty rotating work table with positive gear motor drive - up to 220 lb. load capacity

# WashMaster™ Series

Ransohoff's Washmaster spray cabinet line is a series of high performance, economically priced parts washers designed for years of trouble free service in the most demanding industrial environments.

These rugged machines are manufactured in high-grade stainless steel for all wetted surfaces. This eliminates the corrosion and limited life expectancy problems associated with conventional carbon steel spray cabinets.

Washmaster spray cabinets are ideal parts washers for Job Shops, General Manufacturing, Maintenance and Automotive Rebuild and Remanufacturing applications.

## TECHNICAL SPECIFICATIONS

### Standard Features - Both Models

- 304 Stainless Steel Construction
- Automatic Timer Controlled Cleaning Cycle
- Motor Driven Basket Rotation
- Low Water Level Safety Cut-off
- Disc Type Oil Skimmer
- Stainless Steel Water Circuit and Parts Basket
- Shock Assisted Door for Ease of Loading
- Automatic Safety Shut-off on Load Door
- Heavy-duty Stainless Steel Heating Element
- Stainless Steel Spray Pumps
- Stainless Steel Suction Guards

	CW23 Model	CW35 Model
Basket Diameter (Internal)	23"	35"
Max. Part Height	13"	19"
Max. Load Weight	220 lbs.	440 lbs.
Water Heater	3 kW	6 kW
Washing Temperature	130-170 °F	130-170 °F
Spray Pressure	30 PSI	35 PSI
Pump Output	15 GPM	50 (2 x 25) GPM
Tank Capacity	13 Gallons	37 Gallons
Voltage (AC)	220 Volts -1PH-60 Hz	220 Volts -1PH-60 Hz
Required Power	3.5 kW	7.5 kW
Required Amperage	20.5 Amps (single phase)	43 Amps (single phase)
Sound Level	Less than 70 db(A)	Less than 70 db(A)
Dry Weight	Approx. 150 lbs.	Approx. 300 lbs.

Machine Specifications Subject to Change without Notice



Ransohoff  
Ransohoff Specialty Chemicals Group

Blackstone~NEY Ultrasonics  
Ransohoff Environmental Systems Group

CTG MEDICAL

## RANSOHOFF

Providing Tomorrow's Cleaning Technology Today

A Division of Cleaning Technologies Group, LLC  
(800) 248-9274



ISO - 9001:2000 FM 64783  
ISO - 14001:2004 EMS 64588

**Ransohoff**  
4933 Provident Drive  
Cincinnati, Ohio 45246  
Tel: (513) 870-0100  
Fax: (513) 870-0105  
EMAIL: info@ransohoff.com  
www.ransohoff.com

**Blackstone~NEY Ultrasonics**  
9 N. Main Street  
Jamestown, New York 14702-0220  
Tel: (716) 665-2340 | (800) 766-6606  
Fax: (716) 664-7260  
EMAIL: info@blackstone-ney.com  
www.blackstone-ney.com

