



LeanDrum CF (Cold Forming)

- Wash, Rinse and Blow-off in a small package
- Both Spray & full immersion cleaning
- Stainless Steel Drum, Tanks & Housings
- Easy drum access
- Low cost maintenance
- Perforated Drum Shell
- Longer bath life
- 3-2-1 Warranty
- Designed for Cold forming applications but excellent for most mass products that are turned or stamped.

LeanDrum CF

All specifications are subject to change without notice



CLEANING TECHNOLOGIES GROUP

RANSOHOFF • BLACKSTONE-NEY ULTRASONICS • CTG ASIA

MODEL NUMBER	LD-CF
PART PRODUCTION	12 CU FT/Hour @ 2RPM design drum speed vs Drive 1 - 3 RPM
WASH CAPACITY	100 Gallons (380 Liters)
RINSE CAPACITY	70 Gallons (266 Liters)
BLOWER CAPACITY	470 CFM @ 3" SP
DRUM DIAMETER	18" (457mm)
LOAD HEIGHT	34" (864mm)
UNLOAD HEIGHT	30" (762mm)
FLOOR SPACE (L x W x H)	9' 7" x 4' 7" x 5' 0" (2920 mm X 1400mm X 1525mm)
UTILITY REQUIREMENTS	460V 3 Ph, 60 Hz

Ransohoff
 (800) 248-9274
 4933 Provident Drive
 Cincinnati, OH 45246
www.ctgclean.com

Blackstone-NEY Ultrasonics
 (800) 766-6606
 P.O. Box 220
 9 N. Main St.
 Jamestown, NY 14702-0220

CTG Asia
 (86)0512-66161698
 56 Songshan Road
 Suzhou New District
 Jiangsu Province, China PRC: 215151